

# HEPU/MAXXUS G11 Coolant

## ACL P/N: 1540/1540D/B-1540L



HEPU G11 is a longlife antifreeze and anti-corrosion for use in modern engines. VW number is ZVW 237 105 / G11, up to 1996. For all BMW, Mercedes & Volvo.

### USES

#### Antifreeze Coolant

Recommended for cars for which the manufacturer recommend a "G11" fluid. Suitable for cast iron & aluminium engines.

### PERFORMANCES

#### Meets the requirements of manufacturers warranties requirements

- AUDI: ZVW 237 105
- AUDI: VW-TL 774C
- BMW: N 600 69.0
- BMW: 82 12 1 467 704
- GM / SAAB: 1825M / 690 1599
- MB: 325.0
- MINI: N 600 69.0
- VOLKSWAGEN: ZVW 237 105
- VOLKSWAGEN: VW-TL 774C
- VOLVO: 1286083

### CUSTOMER BENEFITS

#### \* Developed for 8 years replacement intervals.

- \* Made in Germany
- \* Can not be mixed with G12.

- Protection against corrosion & cavitation.
- Prevents sedimentation & foam formation.
- Prevents damage to hoses and seals.
- Can be used with aluminium heads & coolers.
- Premium quality, nitride, amine & phosphate free.

### CHARACTERISTICS

ACL 1540/1540D/B-1540L	Test method	Typical value
Density, at 20°C, g/ml	DIN 51757	1,121-1,125
Color	Visual	Blue
Viscosity, mm <sup>2</sup> /s at 20°C	DIN 51562	20-30
Boiling Point, °C	ASTM D 1120	>165
Melting point @ 1:1, °C	ISO 3016	-15
Flash point °C	DIN 51758	>120
PpH value (33% in water, 20°C)	ASTM D 1287	8,2

The characteristics shown are mean values.

AUTO-CAMPING LTD  
100 Venture Drive  
Scarborough, On, M1B 3L6, Canada

ACL P/N: 1540/1540D/B-1540L

May 2012



This lubricant used according to our recommendations and for its designed application does not represent any particular risk. A safety data sheet in conformity with the legislation now current in Canada is available from your local sales advisor.